查询MR27V6402D供应商

OKI Semiconductor

1A

MR27V6402D Preliminary

4,194,304-Word x 16-Bit or 8,388,608-Word x 8-Bit One Time PROM

DESCRIPTION

The MR27V6402D is a 64Mbit electrically Programmable Read-Only Memory whose configuration can be electrically switched between 4,194,304 word x 16bit and 8,388,608 word x 8bit. The MR27V6402D operates on a single +3V-3.3V power supply and is TTL compatible. Since the MR27V6402D operates asynchronously , external clocks are not required , making this device easy-to-use. The MR27V6402D is suitable as large-capacity fixed memory for microcomputers and data terminals. It is manufactured using a CMOS double silicon gate technology and is offered in 44-pin SOP package.

FEATURES

- 4,194,304 word x 16bit / 8,388,608 word x 8bit electrically switchable configuration
- Single +3V-3.3V power supply
- Access time 150ns access time (Vcc=+3V)
  120ns access time (Vcc=+3.3V)
- Input / Output TTL compatible
- Three-state output
- Package
  44-pin plastic SOP (SOP44-P-600-1.27-K)

PIN CONFIGURATION (TOP VIEW)



44-pin SOP

PIN NAMES	FUNCTIONS
D15/A-1	Data output / Address input
A0-A21	Address input
D0-D14	Data output
$\overline{CE}$	Chip enable
$\overline{OE}$	Output enable
V_{CC}	Power supply voltage
V_{SS}	GND
$\overline{BYTE}/V_{PP}$	Mode switch / Program power supply voltage

BLOCK DIAGRAM



In 8-bit output mode, these pins are three-stated and pin D15 functions as the A-1 address pin.

FUNCTION TABLE

MODE	$\overline{CE}$	$\overline{OE}$	$\overline{BYTE}/V_{PP}$	V_{CC}	D0 - D7	D8 - D14	D15/A-1
READ (16-Bit)	L	L	H	3.0V to 3.3V	D_{OUT}		
READ (8-Bit)	L	L	L		D_{OUT}	Hi-Z	L/H
OUTPUT DISABLE	L	H	H		Hi-Z		
			L				*
STAND-BY	H	*	H		Hi-Z		
			L				*
PROGRAM	L	H	9.75V	4.0V	D_{IN}		
PROGRAM INHIBIT	H	H			Hi-Z		
PROGRAM VERIFY	H	L			D_{OUT}		

*: Don't Care

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Condition	Value	Unit
Operating temperature under bias	Topr	-	0 to 70	°C
Storage temperature	T_{stg}		-55 to 125	°C
Input voltage	V_I	relative to V_{SS}	-0.5 to V_{CC}+ 0.5	V
Output voltage	V_O		-0.5 to V_{CC} +0.5	V
Power supply voltage	V_{CC}		-0.5 to 5	V
Program power supply voltage	V_{PP}		-0.5 to 11.5	V
Power dissipation per package	P_D	-	1.0	W

RECOMMENDED OPERATING CONDITIONS

(Ta=0 to 70°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
V_{CC} power supply voltage	V_{CC}	V_{CC}=2.7V-3.6V	2.7	-	3.6	V
V_{PP} power supply voltage	V_{PP}		-0.5	-	V_{CC}+0.5	V
Input "H" level	V_{IH}		2.2	-	V_{CC}+0.5	V
Input "L" level	V_{IL}		-0.5	-	0.6	V

Voltage is relative to Vss

ELECTRICAL CHARACTERISTICS (Read operation)

DC Characteristics 1

(V_{CC}=3V±0.3V, Ta=0 to 70°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Input leakage current	I_{LI}	V_I=0 to Vcc	-	-	10	µA
Output leakage current	I_{LO}	V_O=0 to Vcc	-	-	10	µA
V_{CC} power supply current (Standby)	I_{CCSC}	$\overline{CE}$=V_{CC}	-	-	50	µA
	I_{CCST}	$\overline{CE}$=V_{IH}	-	-	1	mA
V_{CC} power supply current (Read)	I_{CCA}	$\overline{CE}$=V_{IL}, $\overline{OE}$=V_{IH} tc=150ns	-	-	45	mA
V_{PP} power supply current	I_{PP}	V_{PP}=V_{CC}	-	-	10	µA
Input "H" level	V_{IH}	-	2.2	-	V_{CC}+0.5	V
Input "L" level	V_{IL}	-	-0.5	-	0.6	V
Output "H" level	V_{OH2}	I_{OH}=-200uA	V_{CC}-0.4	-	-	V
Output "L" level	V_{OL2}	I_{OL}=1mA	-	-	0.4	V

Voltage is relative to Vss

DC Characteristics 2

(V_{CC}=3.3V±0.3V, Ta=0 to 70°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Input leakage current	I_{LI}	V_I=0 to Vcc	-	-	10	µA
Output leakage current	I_{LO}	V_O=0 to Vcc	-	-	10	µA
V_{CC} power supply current (Standby)	I_{CCSC}	$\overline{CE}$=V_{CC}	-	-	50	µA
	I_{CCST}	$\overline{CE}$=V_{IH}	-	-	1	mA
V_{CC} power supply current (Read)	I_{CCA}	$\overline{CE}$=V_{IL}, $\overline{OE}$=V_{IH} tc=120ns	-	-	50	mA
V_{PP} power supply current	I_{PP}	V_{PP}=V_{CC}	-	-	10	µA
Input "H" level	V_{IH}	-	2.2	-	V_{CC}+0.5	V
Input "L" level	V_{IL}	-	-0.5	-	0.6	V
Output "H" level	V_{OH2}	I_{OH}=-200µA	V_{CC}-0.4	-	-	V
Output "L" level	V_{OL2}	I_{OL}=1mA	-	-	0.4	V

Voltage is relative to Vss

AC Characteristics 1

(V_{CC}=3V±0.3V, Ta=0 to 70°C)

Parameter	Symbol	Condition	Min.	Max.	Unit
Address cycle time	T_C	-	150	-	ns
Address access time	T_{ACC}	$\overline{CE}$=$\overline{OE}$=V_{IL}	-	150	ns
$\overline{CE}$ access time	T_{CE}	$\overline{OE}$=V_{IL}	-	150	ns
$\overline{OE}$ access time	T_{OE}	$\overline{CE}$=V_{IL}	-	60	ns
Output disable time	T_{CHZ}	$\overline{OE}$=V_{IL}	0	50	ns
	T_{OHZ}	$\overline{CE}$=V_{IL}	0	45	ns
Output hold time	T_{OH}	$\overline{CE}$=$\overline{OE}$=V_{IL}	0	-	ns

Measurement conditions

Input signal level ---------- 0V/3V
Input timing reference level ---------- 0.8V/2.0V
Output load ---------- 100pF
Output timing reference level ---------- 0.8V/2.0V

AC Characteristics 2

(V_{CC}=3.3V±0.3V, Ta=0 to 70°C)

Parameter	Symbol	Condition	Min.	Max.	Unit
Address cycle time	T_C	-	120	-	ns
Address access time	T_{ACC}	$\overline{CE}$=$\overline{OE}$=V_{IL}	-	120	ns
$\overline{CE}$ access time	T_{CE}	$\overline{OE}$=V_{IL}	-	120	ns
$\overline{OE}$ access time	T_{OE}	$\overline{CE}$=V_{IL}	-	50	ns
Output disable time	T_{CHZ}	$\overline{OE}$=V_{IL}	0	40	ns
	T_{OHZ}	$\overline{CE}$=V_{IL}	0	35	ns
Output hold time	T_{OH}	$\overline{CE}$=$\overline{OE}$=V_{IL}	0	-	ns

Measurement conditions

Input signal level ---------- 0V/3V
Input timing reference level ---------- 0.8V/2.0V
Output load ---------- 100pF
Output timing reference level ---------- 0.8V/2.0V



TIMING CHART (READ CYCLE)

16-Bit Read Mode ($\overline{BYTE}$=V_{IH})



8-Bit Read Mode ($\overline{BYTE}$=V_{IL})



ELECTRICAL CHARACTERISTICS (Programming operation)

DC Characteristics

(Ta=25°C±5°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Input leakage current	I_{LI}	$V_I=V_{CC}+0.5V$	-	-	10	µA
V_{PP} power supply current (Program)	I_{PP2}	$\overline{CE}=V_{IL}$	-	-	50	mA
V_{CC} power supply current	I_{CC}	-	-	-	50	mA
Input "H" level	V_{IH}	-	3.0	-	$V_{CC}+0.5$	V
Input "L" level	V_{IL}	-	-0.5	-	0.8	V
Output "H" level	V_{OH}	$I_{OH}=-400µA$	2.4	-	-	V
Output "L" level	V_{OL}	$I_{OL}=2.1mA$	-	-	0.45	V
Program voltage	V_{PP}	-	9.5	9.75	10.0	V
V_{CC} power supply voltage	V_{CC}	-	3.9	4.0	4.1	V

Voltage is relative to Vss

AC Characteristics

(V_{cc}=4.0V±0.1V,V_{pp}=9.75V±0.25V,Ta=25°C±5°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Address set-up time	T_{AS}	-	100	-	-	ns
$\overline{OE}$ set-up time	T_{OES}	-	2	-	-	µs
Data set-up time	T_{DS}	-	100	-	-	ns
Address hold time	T_{AH}	-	2	-	-	µs
Data hold time	T_{DH}	-	100	-	-	ns
Output float delay from $\overline{OE}$	T_{OHZ}	-	0	-	100	ns
V_{PP} voltage set-up time	T_{VS}	-	2	-	-	µs
Program pulse width	T_{PW}	-	9	10	11	µs
Data valid from $\overline{OE}$	T_{OE}	-	-	-	100	ns
Address hold from $\overline{OE}$ high	T_{AHO}	-	0	-	-	ns

Pin Check Function

Pin Check Function is to check contact between each device-pin and each socket-lead with EPROM programmer.

Setting up address as the following condition call the preprogrammed codes on device outputs.

(V_{cc}=3.3V±0.3V,$\overline{CE}$=$\overline{OE}$=V_{IL},$\overline{BYTE}$/V_{pp}=V_{IH},Ta=25°C±5°C)

A0	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12	A13	A14	A15	A16	A17	A18	A19	A20	A21	DATA
0	1	0	1	0	1	0	1	0	VH*	0	1	0	1	0	1	0	0	1	1	0	0	FF00
1	0	1	0	1	0	1	0	1	VH*	1	0	1	0	1	0	1	1	0	0	1	1	00FF
Other conditions																						FFFF

* :VH=8V±0.25V

Consecutive Programming Waveforms



Consecutive Program Verify Waveforms



Program and Program Verify Cycle Waveforms



PIN Capacitance

(V_{CC}=3.3V, Ta=25°C, f=1MHz)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Input	C_{IN1}	V_I=0V	-	-	12	pF
$\overline{BYTE}/V_{PP}$	C_{IN2}		-	-	120	
Output	C_{OUT}	V_O=0V	-	-	15	

Programming / Verify Flow Chart



NOTICE

The information contained herein can change without notice owing to product and/or technical improvements. Before using the product, please make sure that the information being referred to is up-to-date.

The outline of action and examples for application circuits described herein have been chosen as an explanation for the standard action and performance of the product. When planning to use the product, please ensure that the external conditions are reflected in the actual circuit, assembly, and program designs.

When designing your product, please use our product below the specified maximum ratings and within the specified operating ranges including, but not limited to, operating voltage, power dissipation, and operating temperature.

Oki assumes no responsibility or liability whatsoever for any failure or unusual or unexpected operation resulting from misuse, neglect, improper installation, repair, alteration or accident, improper handling, or unusual physical or electrical stress including, but not limited to, exposure to parameters beyond the specified maximum ratings or operation outside the specified operating range.

Neither indemnity against nor license of a third party's industrial and intellectual property right, etc. is granted by us in connection with the use of the product and/or the information and drawings contained herein. No responsibility is assumed by us for any infringement of a third party's right which may result from the use thereof.

The products listed in this document are intended for use in general electronics equipment for commercial applications (e.g., office automation, communication equipment, measurement equipment, consumer electronics, etc.). These products are not authorized for use in any system orapplication that requires special or enhanced quality and reliability characteristics nor in any system or application where the failure of such system or application may result in the loss or damage of property, or death or injury to humans. Such applications include, but are not limited to, traffic and automotive equipment, safety devices, aerospace equipment, nuclear power control, medical equipment, and life-support systems.

Certain products in this document may need government approval before they can be exported to particular countries. The purchaser assumes the responsibility of determining the legality of export of these products and will take appropriate and necessary steps at their own expense for these.

No part of the contents cotained herein may be reprinted or reproduced without our prior permission.

All brand, company and product names are the trademarks or registered trademarks of their respective owners.

Copyright 1998 Oki Electric Industry Co., Ltd.
Marketing Communications Team (RB)

People To People Technology

ADDRESSES & SEMICONDUCTOR WEB SITES

OKI Electric Industry Co., Ltd.,
Device Business Group,
10-3, Shibaura, 4-chome,
Minato-ku, Tokyo 108, Japan,
Tel.: +81-(0)3-5445-6327,
Fax.: +81-(0)3-5445-6328,
http://www.oki.co.jp/semi/

OKI Semiconductor Group,
785 North Mary Avenue,
Sunnyvale, CA 94086, U.S.A.,
Tel.: +1-408-720-1900,
Fax.: +1-408-720-1918,
http://www.okisemi.com/

OKI Electric Europe GmbH,
Head Office Europe,
Hellersbergstrasse 2,
D-41460 Neuss, Germany,
Tel: +49-2131-15960,
Fax: +49-2131-103539,
http://www.oki-europe.de/

OKI Electronics (Hong Kong) Ltd.,
Suite 1901-1&19, Tower 3,
China Hong Kong City,
33 Canton Road, Tsimshatsui,
Kowloon, Hong Kong,
Tel.: +852-2-736-2336,
Fax.: +852-2-736-2395

OKI Semiconductor (Asia) Pte. Ltd.,
78 Shenton Way 09-01,
Singapore 0207,
Tel.: +65-221-3722,
Fax.: +65-323-5376

OKI Semiconductor (Asia) Pte. Ltd.,
Taipei Branch,
7th Fl. No.260, Tun Hwa North Road,
Taipei, Taiwan, R.O.C.,
Sumitomo-Flysun Building,
Tel.: +886-2-2719-2561,
Fax.: +886-2-2715-2892
http://www.oki.net.tw/

For further information, please contact: